Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-201-6471

# **Body Style:**

Straight shape, external coupling

# **Overall Length:**

1.100 inches

# **Overall Height:**

1.812 inches

# **Overall Width:**

1.812 inches

## **Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

# **Unthreaded Mounting Hole Diameter:**

# 0.147 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

# 1.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.500 inches

# **Distance From Mounting Shoulder To Front Face:**

0.790 inches

# Mating End Quantity:

1

## **Contact Removability:**

Removable single mating end all contact groupings

## **Polarization Method:**

Keyway or multiple keyway

## **Insert Position In Deg:**

345.0

## Shell Type:

Solid

## **Connector Locking Method:**

Bayonet pin

## **End Application:**

1520-01-106-9519

## **Terminal Location:**

Back single mating end all contact groupings

## **Contact Material:**

Copper alloy single mating end all contact groupings

## **Contact Surface Treatment:**

Gold single mating end all contact groupings

## **Terminal Type:**

Crimp single mating end all contact groupings

## **Shell Material:**

Aluminum alloy

# NSN 5935-01-201-6471

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:

#### Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

## Included Contact Quantity:

8 single mating end 1st contact grouping

#### Included Contact Type:

Round pin single mating end all contact groupings

#### Precious Material And Location:

Contact surfaces gold

**Precious Material And Weight:** 

0.056 gold grains, troy

Precious Material:

Gold

#### **Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

96906-ms27505 government standard

Shelf Life:

N/a

## Unit Of Measure:

--

#### **Demilitarization:**

No

#### Fiig:

A039b0

#### Mil-std (military Standard):

Mil-c-38999 spec.