Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-201-6480

Thread Class:
2a and 2b and 2a
Thread Direction:
Right-hand and right-hand and right-hand
Body Style:
Straight shape
Overall Length:
1.070 inches
Overall Height:
0.620 inches
Overall Width:
0.280 inches
Environmental Protection:
Humidity resistant and shock resistant and thermal shock resistant and vibration resistant
Distance Between Mounting Facility Centers:
0.814 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
20 20-20 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
56 and 56 and 56
Thread Size:
0.086 inches and 0.086 inches and 0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end

## NSN 5935-01-201-6480

Electrical Receptacle Connector - Page 2 of 2



**Contact Surface Treatment Specification:** Mil-g-45204, type 1, grade c military specification single treatment response single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Insert Material Specification:** Mil-m-14, ty sdg-f military specification single material response single mating end Unable To Decode: Unable to decode and unable to decode **Included Contact Quantity:** 20 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Special Features:** Capable of being mounted on a 0.090 in. Thick panel **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.020 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc and unc and unc Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.