## NSN 5935-01-201-6482

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-201-6482

Body Style:
Straight shape
Overall Length:
Between 2.620 inches and 2.650 inches
Overall Height:
0.683 inches
Overall Width:
Between 0.590 inches and 0.620 inches
Unthreaded Mounting Hole Diameter:
0.086 inches
Distance Between Mounting Facility Centers:
Between 2.401 inches and 2.411 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
50 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, ty ii, gr c, cl 1 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Metal
Shell Surface Treatment:

Cadmium

**Shell Surface Treatment Specification:** 

Qq-p-416, type 2, cl 2 federal specification single treatment response

## NSN 5935-01-201-6482

Electrical Receptacle Connector - Page 2 of 2



Insert Material	Specification:
-----------------	----------------

Mil-m-14, ty sdg-f military specification single material response single mating end

**Included Contact Quantity:** 

50 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.050 gold grains, troy

**Precious Material:** 

Gold

## **Test Data Document:**

81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-c-24308/2 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.