NSN 5935-01-202-4382

Thread Class: 2b and 2a

Right-hand
Body Style:
Straight type
Overall Length:
2.650 inches
Overall Height:

Thread Direction:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-202-4382

0.685 inc	hes
Overall V	Nidth:
0.250 inc	hes
Environr	mental Protection:
Vibration	resistant and humidity resistant and corrosion resistant
Unthread	ded Mounting Hole Diameter:
0.120 inc	hes
Distance	Between Mounting Facility Centers:
2.400 inc	hes
Threade	d Device Type:
Coupling	facility
Mating E	ind Quantity:
1	
Contact	Position Arrangement Style:
2 rows of	contacts non-inserted board single mating end
Contact	Removability:
Nonremo	vable single mating end single contact grouping
Contact	Maximum Current Rating In Amps:
5.0 single	e mating end single contact grouping
Polarizat	tion Method:
Jackscre	w
Connect	or Locking Method:
Jackscre	w-socket
Thready	Qty Per Inch (tpi):
56	
Thread S	Size:
0.086 inc	hes
Terminal	Location:
Back sing	gle mating end single contact grouping
Contact	Material:
Copper a	lloy single mating end single contact grouping
Contact	Surface Treatment:
Coldaina	gle mating end single contact grouping and nickel single mating end single contact grouping

NSN 5935-01-202-4382

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment Specification:

Mil-g-45204, ty ii, grade c, class 00 military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 2 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

36 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Jackscrew type-male and location-right hand topandjackscrew type-female and location-left hand bottom

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.036 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.