Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-202-6199

### **Body Style:**

Straight shape, external coupling

### **Overall Length:**

1.390 inches

## **Overall Diameter:**

0.870 inches

### **Environmental Protection:**

Shock proof and vibration proof

### **Cable Entrance Diameter:**

0.425 inches

## **Threaded Device Type:**

Coupling facility

## Mating End Quantity:

1

### **Contact Position Arrangement Style:**

N single mating end

## Contact Removability:

Removable single mating end single contact grouping

### Shell Type:

Solid

# **Connector Locking Method:**

Externally threaded shell

# Connector Cable Strain Relief Method:

Compression nut

# Radio Frequency Type Contact Characteristic Impedance In Ohms:

75.0 single mating end single contact grouping

### **Terminal Location:**

Back single mating end single contact grouping

# **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping

## **Terminal Type:**

Crimp single mating end single contact grouping

### Shell Material:

Copper alloy

### **Included Contact Quantity:**

1 single mating end single contact grouping

### Included Contact Type:

Coaxial socket single mating end single contact grouping

### **Special Features:**

Solder flange mtd



**Precious Material And Location:** 

Contact surface gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0