

View Online at <https://aerobasegroup.com/nsn/5935-01-202-8376>

Thread Class:

2a and 2b

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, internal coupling w/backshell

Overall Length:

1.234 inches

Overall Diameter:

1.406 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

17-55 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Thready Qty Per Inch (tpi):

20

Thread Size:

0.938 inches and 25.0 millimeters

Thread Pitch In Millimeters:

1.00

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Nickel and lacquer

Shell Surface Treatment Specification:

Mil-c-26074 military specification 1st treatment response

Thread Tolerance Class:

6g internal

Included Contact Quantity:

55 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Shell coated with two coats acrylic gray lacquer

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.055 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef and iso m

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-26074 spec.