

View Online at <https://aerobasegroup.com/nsn/5935-01-202-8414>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling w/backshell

Overall Length:

1.320 inches

Overall Height:

1.219 inches

Overall Width:

1.219 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Unthreaded Mounting Hole Diameter:

0.128 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.968 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.968 inches

Distance From Mounting Shoulder To Front Face:

0.820 inches

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

15-35 single mating end

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

326.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thread Length:

0.219 inches

Thready Qty Per Inch (tpi):

20

Thread Size:

0.812 inches

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

96906-ms27656 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-38999 spec.