

View Online at <https://aerobasegroup.com/nsn/5935-01-203-1119>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.289 inches

**Overall Height:**

1.219 inches

**Overall Width:**

1.219 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.969 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.969 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.815 inches and 0.820 inches

**Threaded Device Type:**

Back shell

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

15-35 single mating end

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

326.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Thread Length:**

0.219 inches

**Thready Qty Per Inch (tpi):**

20

**Thread Size:**

0.812 inches

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response

**Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef

**Specification Data:**

96906-ms27656 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-c-38999 spec.