Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-203-3261

View Online at https://aerobasegroup.com/nsn/5935-01-203-3261
Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.000 inches
Overall Diameter:
0.870 inches
Cable Entrance Diameter:
0.170 inches
Mounting Facility Thickness:
0.187 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
Bnc single mating end
Contact Removability:
Removable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Connector Cable Strain Relief Method:
Compression nut
Thready Qty Per Inch (tpi):
24
Thread Size:
0.625 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic polytetrafluoroethylene single mating end
Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping



	inal Type:
	p single mating end single contact grouping
	act Material Specification:
	-530 federal specification single material response single mating end single contact grouping
	I Material:
	ber alloy
	I Material Specification:
-	-626 federal specification single material response
	rt Material Specification:
	03 federal specification single material response single mating end
	ded Contact Quantity:
	gle mating end single contact grouping
	ning Accommodation Hole Shape:
	nd w/flat
Inclu	ded Contact Type:
	ial socket single mating end single contact grouping
Prec	ious Material And Location:
Conta	act surface gold
Prec	ious Material And Weight:
0.005	5 gold grains, troy
Prec	ious Material:
Gold	
Thre	ad Series Designator:
Unef	
Shel	f Life:
N/a	
Unit	Of Measure:
Dem	ilitarization:
No	
Fiig:	
A039	b0
Mil-s	td (military Standard):
Mil-a	-45204 spec.