## NSN 5935-01-203-3543

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-203-3543

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
4.795 inches
Overall Height:
0.907 inches
Overall Width:
0.590 inches
Distance Between Mounting Facility Centers:
4.475 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Contact to contact polarizing keys
Thready Qty Per Inch (tpi):
40
Thread Size:
0.112 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping
Terminal Type:
Wire wrap single mating end single contact grouping
Included Contact Quantity:

moraded Comact Quartity

148 single mating end single contact grouping

## NSN 5935-01-203-3543

Electrical Receptacle Connector - Page 2 of 2



<b>Precious Material And Location:</b>
Contact surfaces gold
<b>Precious Material And Weight:</b>
0.148 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.