NSN 5935-01-203-3949

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-203-3949

Body Style:
Straight type
Overall Length:
4.900 inches
Overall Height:
0.677 inches
Overall Width:
0.400 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
4.650 inches
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1200.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Glass single mating end and plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2 military specification single treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:
Qq-b-626 federal specification single material response single mating end single contact grouping
Guide Design And Location:
D shape socket right-hand at 12 oclock
Included Contact Quantity:
122 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

NSN 5935-01-203-3949

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location
Contact surfaces gold
Precious Material And Weight:
0.122 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.