

View Online at https://aerobasegroup.com/nsn/5935-01-203-3991

# Thread Class:

2b and 2a and 2a

# **Thread Direction:**

Right-hand and right-hand and right-hand

# **Body Style:**

Rectangular shape center screwlock

### **Overall Length:**

1.334 inches

### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.084 inches

### **Overall Height:**

0.560 inches

### **Overall Width:**

0.450 inches

### **Environmental Protection:**

Humidity resistant and shock resistant and vibration resistant and fungus proof

# **Unthreaded Mounting Hole Diameter:**

0.120 inches

# Threaded Device Type:

Coupling facility and back shell

### Mating End Quantity:

12

# **Contact Position Arrangement Style:**

12 single mating end

### **Polarization Method:**

Polarization boss and guide pin/socket

### **Connector Locking Method:**

Post jacksocket

# Thready Qty Per Inch (tpi):

40 and 40 and 32

### Thread Size:

0.112 inches and 0.138 inches

### **Insert Material:**

Plastic diallyl phthalate single mating end or plastic epoxy single mating end or plastic phenolic single mating end

### **Insert Material Specification:**

Mil-m-14, type sdg-f military specification single material response single mating end or mil-p-19833, type gdi-30f military specification single material response single

### **Thread Series Designator:**

Unc and unc and unc

### Shelf Life:

N/a

## Unit Of Measure:



Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.