NSN 5935-01-203-5770

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-203-5770
Body Style:
Hood, top opening w/clamp
Overall Length:
Between 2.610 inches and 2.630 inches
Overall Height:
1.860 inches
Overall Width:
0.290 inches
Environmental Protection:
Humidity resistant and salt water resistant and thermal shock resistant and vibration resistant
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Hood, top opening
Connector Locking Method:
Friction
Connector Cable Strain Relief Method:
Cable clamp
End Application:
An/sps-6 (v) 1
Cable Opening Length:
1.590 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204, type 2, class 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290,
class 1 federal specification 2nd treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize

Shell Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

NSN 5935-01-203-5770

Electrical Plug Connector - Page 2 of 2



Included Contact Quantity:
40 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.040 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-28754 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-28754/32 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Δ ∩30h Ω

7100000

Mil-std (military Standard):

Mil-g-45204 spec.