

View Online at <https://aerobasegroup.com/nsn/5935-01-203-8792>

Body Style:

Embase male, w/fingers and guides

Environmental Protection:

Corrosion resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

45 all mating ends

Contact Removability:

Removable all mating ends single contact grouping

Contact Maximum Current Rating In Amps:

3.0 all mating ends single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1000.0 all mating ends single contact grouping

Polarization Method:

2 polarization posts

Radio Frequency Type Contact Characteristic Impedance In Ohms:

6.0 all mating ends single contact grouping

Contact Material:

Beryllium all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 military specification 2nd treatment response all mating ends single contact grouping

Terminal Type:

Tapered pin all mating ends single contact grouping

Contact Material Specification:

Qq-c-533 federal specification 1st material response all mating ends single contact grouping

Guide Design And Location:

D shape pin left-hand at 12 oclock

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.