

View Online at <https://aerobasegroup.com/nsn/5935-01-204-0489>

Body Style:

Straight edge type w/mounting flange

Overall Length:

3.200 inches

Overall Height:

0.810 inches

Overall Width:

0.440 inches

Environmental Protection:

Fire resistant and humidity resistant and shock resistant and thermal shock resistant

Unthreaded Mounting Hole Diameter:

0.116 inches

Distance Between Mounting Facility Centers:

2.950 inches

Board Accommodated Length:

2.520 inches single board

Board Accommodated Width:

0.094 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, ty ii, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty gdi-30f military specification single material response single mating end

Included Contact Quantity:

30 single mating end single contact grouping

Included Contact Type:

Bifurcated spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.030 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.