

View Online at <https://aerobasegroup.com/nsn/5935-01-204-0490>

Body Style:

Straight shape

Overall Length:

1.721 inches

Overall Height:

1.000 inches

Overall Width:

1.275 inches

Environmental Protection:

Heat resistant and cold resistant and vibration resistant and shock resistant

Unthreaded Mounting Hole Diameter:

0.125 inches

Distance Between Mounting Facility Centers:

1.375 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

750.0 single mating end single contact grouping

Polarization Method:

Contact to contact polarizing keys

Shell Type:

Solid

Connector Locking Method:

Latching ring

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

Unable To Decode:

Unable to decode and unable to decode

Terminal Type:

Tab, solder lug single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Nickel

Included Contact Quantity:

8 single mating end single contact grouping

Included Contact Type:

Flat pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.008 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.