NSN 5935-01-204-1378

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-204-1378
Thread Class:
2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
1.370 inches
Overall Diameter:
0.987 inches
Environmental Protection:
Humidity resistant and salt water resistant and shock proof and vibration proof
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
14-7 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Thready Qty Per Inch (tpi):
20 and 20
Thread Size:
0.875 inches and 0.938 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end

NSN 5935-01-204-1378

Electrical Plug Connector - Page 2 of 2



Contact Surface Treatment Specification: Mil-g-45204, type 1, cl 2 military specification single treatment response single mating end single contact grouping **Criticality Code Justification:** Feat **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Nickel **Shell Material Specification:** Qq-a-367 federal specification single material response **Included Contact Quantity:** 7 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Special Features:** Heavier nickel plating required for emi/rfi protection **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.007 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef and unef Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.