Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-204-1396

#### **Body Style:**

Straight shape, external coupling

### **Overall Length:**

1.099 inches

# **Overall Height:**

1.438 inches

# **Overall Width:**

1.438 inches

#### **Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

#### **Unthreaded Mounting Hole Diameter:**

Between 0.123 inches and 0.138 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Height:

1.156 inches

#### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.156 inches

## Distance From Mounting Shoulder To Front Face:

Between 0.815 inches and 0.820 inches

## Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

19-35 single mating end

#### **Contact Removability:**

Removable single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### **Insert Position In Deg:**

30.0

#### Shell Type:

Solid

#### **Connector Locking Method:**

Bayonet pin

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping

## **Terminal Type:**

Crimp single mating end single contact grouping

# Shell Material:

Aluminum alloy

# NSN 5935-01-204-1396

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:

#### Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

# Included Contact Quantity:

66 single mating end single contact grouping

## Included Contact Type:

Round pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:** 

0.066 gold grains, troy

Precious Material:

Gold

#### **Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

96906-ms27505 government standard

Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

## Fiig:

A039b0

#### Mil-std (military Standard):

Mil-c-38999 spec.