Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-205-0058

Thread Class:
2a Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Height:
2.500 inches
Overall Width:
2.500 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof and shock proof
Unthreaded Mounting Hole Diameter:
Between 0.194 inches and 0.202 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.937 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.937 inches
Distance From Mounting Shoulder To Front Face:
0.878 inches
Threaded Device Type:
Back shell
Mating End Quantity:
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
2350-01-087-1097 cmbt85-m1e1, armored battle tank
Thread Length:
0.467 inches
Thready Qty Per Inch (tpi):
16

## NSN 5935-01-205-0058

Electrical Receptacle Connector - Page 2 of 2



	-
Thread Size:	
2.062 inches	
Terminal Location:	
Back single mating end single contact grouping	
Contact Material:	
Copper alloy single mating end single contact grouping	
Contact Surface Treatment:	
Silver single mating end single contact grouping	
Insert Material:	
Rubber single mating end	
Contact Surface Treatment Specification:	
Qq-s-365 federal specification single treatment response single mating end single contact grouping	ļ
Terminal Type:	
Crimp single mating end single contact grouping	
Shell Material:	
Steel	
Shell Surface Treatment:	
Passivate	
Included Contact Quantity:	
48 single mating end single contact grouping	
Included Contact Type:	
Round socket single mating end single contact grouping	
Precious Material And Location:	
Contact surfaces silver	
Precious Material And Weight:	
0.048 silver grains, troy	
Precious Material:	
Silver	
Thread Series Designator:	
Uns	
Specification Data:	
19207-12324289 manufacturers source control	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	