## NSN 5935-01-205-2901



Receptacle Dummy Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-205-2901 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** Between 0.760 inches and 0.800 inches **Overall Height:** 1.437 inches **Overall Width:** 1.437 inches **Environmental Protection:** Corrosion resistant and humidity resistant **Unthreaded Mounting Hole Diameter:** Between 0.116 inches and 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.156 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.156 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.312 inches **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Anodize **Shell Surface Treatment Specification:** 

Mil-a-8625, type 2, cl 2 military specification single treatment response

## **Test Data Document:**

81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Unef

## NSN 5935-01-205-2901

Receptacle Dummy Connector - Page 2 of 2



Specification Data:
81349-mil-c-83723/61 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-a-8625 spec.