NSN 5935-01-205-2901



Receptacle Dummy Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-205-2901 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** Between 0.760 inches and 0.800 inches **Overall Height:** 1.437 inches **Overall Width:** 1.437 inches **Environmental Protection:** Corrosion resistant and humidity resistant **Unthreaded Mounting Hole Diameter:** Between 0.116 inches and 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.156 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.156 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.312 inches **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Anodize **Shell Surface Treatment Specification:**

Mil-a-8625, type 2, cl 2 military specification single treatment response

Test Data Document:

81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

NSN 5935-01-205-2901

Receptacle Dummy Connector - Page 2 of 2



| Specification Data: |
|---|
| 81349-mil-c-83723/61 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |

Mil-std (military Standard):

Mil-a-8625 spec.