Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-205-2909

Thread Class:

2a and 2b and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape

Overall Length:

3.125 inches

Overall Height:

0.844 inches

Overall Width:

0.375 inches

Distance Between Mounting Facility Centers:

2.802 inches

Threaded Device Type:

Coupling facility and mounting stud

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1200.0 single mating end single contact grouping

Polarization Method:

Shell and jackscrew

Connector Locking Method:

Jackscrew-socket

Thready Qty Per Inch (tpi):

40 and 40 and 40

Thread Size:

0.112 inches and 0.112 inches and 0.112 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping



Solder well sing	gle mating end single contact grouping
Insert Materia	I Specification:
Mil-m-14, ty mo	dg military specification single material response single mating end
Shell Guide T	ype And Location Designator:
A pin and a pin	1
Unable To De	code:
Unable to deco	ode and unable to decode
Included Cont	tact Quantity:
50 single matir	ng end single contact grouping
Included Cont	tact Type:
Round pin sing	gle mating end single contact grouping
Special Featu	res:
Jackscrew type	e-female and location-right handandjackscrew type-male and location-left hand
Precious Mate	erial And Location:
Contact surfac	es gold
Precious Mate	erial And Weight:
0.050 gold grai	ins, troy
Precious Mate	erial:
Gold	
Thread Series	Designator:
Unc and unc a	nd unc
Shelf Life:	
N/a	
Unit Of Measu	ıre:
Demilitarizatio	on:
No	
Fiig:	
A039b0	
Mil-std (milita	ry Standard):
Mil-g-45204 sp	ec.