NSN 5935-01-205-2909

Electrical Receptacle Connector - Page 1 of 2



N"
View Online at https://aerobasegroup.com/nsn/5935-01-205-2909
Thread Class:
2a and 2b and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape
Overall Length:
3.125 inches
Overall Height:
0.844 inches
Overall Width:
0.375 inches
Distance Between Mounting Facility Centers:
2.802 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1200.0 single mating end single contact grouping
Polarization Method:
Shell and jackscrew
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
40 and 40 and 40
Thread Size:
0.412 inches and 0.412 inches and 0.412 inches

0.112 inches and 0.112 inches and 0.112 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

NSN 5935-01-205-2909

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Insert Material Specification:
Mil-m-14, ty mdg military specification single material response single mating end
Shell Guide Type And Location Designator:
A pin and a pin
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
50 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Jackscrew type-female and location-right handandjackscrew type-male and location-left hand
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.050 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc and unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: