NSN 5935-01-205-4528

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-205-4528 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.289 inches **Overall Height:** 1.438 inches **Overall Width:** 1.438 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Unthreaded Mounting Hole Diameter:** Between 0.123 inches and 0.138 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.056 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.056 inches **Distance From Mounting Shoulder To Front Face:** Between 0.815 inches and 0.820 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 19-11 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Thread Length:** 0.219 inches

18

Thready Qty Per Inch (tpi):

NSN 5935-01-205-4528

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Thread Size:
1.062 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Criticality Code Justification:
Feat
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Nickel
Shell Surface Treatment Specification:
Mil-c-26074 military specification single treatment response
Included Contact Quantity:
11 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Heavier nickel plating required for emi/rfi protection
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.011 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):