NSN 5935-01-206-1196

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-206-1196 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.471 inches **Overall Height:** 1.000 inches **Overall Width:** 1.000 inches **Environmental Protection:** Corrosion resistant and moisture resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.718 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.718 inches **Distance From Mounting Shoulder To Front Face:** 0.720 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Sc single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.688 inches **Terminal Location:**

Tommar Location

Back single mating end single contact grouping

NSN 5935-01-206-1196

Electrical Receptacle Connector - Page 2 of 2



Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, class 2, type 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder stud single mating end single contact grouping

Contact Material Specification:

Qq-c-530, cond a federal specification single material response single mating end single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Passivate

Shell Surface Treatment Specification:

Mil-f-14072 military specification single treatment response

Shell Material Specification:

Qq-s-764, class 303, cond a federal specification single material response

Insert Material Specification:

Mil-p-19468 military specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.