

View Online at <https://aerobasegroup.com/nsn/5935-01-206-1203>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.552 inches

Overall Diameter:

Between 2.047 inches and 2.078 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and thermal shock resistant and corrosion resistant

Distance From Mounting Shoulder To Front Face:

Between 0.721 inches and 0.772 inches

Mounting Facility Thickness:

Between 0.062 inches and 0.219 inches

Threaded Device Type:

Back shell and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

24-61 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1000.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

180.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thread Length:

0.290 inches and 0.336 inches

Thready Qty Per Inch (tpi):

18 and 18

Thread Size:

1.438 inches and 1.625 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy 6061 or aluminum alloy 380.0 or aluminum alloy a380.0

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

Shell Material Specification:

Qq-a-367, type t6 federal specification 1st material response or qq-a-591 federal specification 2nd material response or qq-a-591 federal specification 3rd material response

Included Contact Quantity:

61 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

In order to complete the connector assembly, the user must obtain/provide the backshell; standard versions may be ordered as nsn 5935-01-174-3669, p/n m85049/52-1-24w for the straight style, or nsn 5935-01-193-8434, p/n m85049/51-1-24w for the right angle style

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.061 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef and unef

Specification Data:

96906-ms3474 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

N/A

Mil-std (military Standard):

Mil-g-45204 spec.