## NSN 5935-01-206-1547

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-206-1547 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Rectangular shape center screwlock **Overall Length:** 2.780 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.460 inches **Overall Height:** 1.123 inches **Overall Width:** 0.725 inches **Environmental Protection:** Heat resistant and pressure proof and shock resistant and vibration resistant **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Thread Size:** 0.138 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Beryllium single mating end single contact grouping and copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Included Contact Quantity:** 88 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping

Throad Sories I

**Special Features:** 

Jackscrew type-female and location-center

**Thread Series Designator:** 

Unc

## NSN 5935-01-206-1547

Electrical Receptacle Connector - Page 2 of 2



| She | lf I | Life | е: |
|-----|------|------|----|
|     |      |      |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0