NSN 5935-01-206-2836

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-206-2836

view Offilite at https://aerobasegroup.com/his//0900-01-200-2000
Body Style:
Right angle type
Overall Length:
6.220 inches
Overall Height:
0.742 inches
Overall Width:
0.507 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
5.900 inches
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Friction
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, ty ii, gr c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal
specification 2nd treatment response single mating end single contact grouping
Terminal Type:
Solder stud single mating end single contact grouping
Contact Material Specification:
Qq-b-626d federal specification single material response single mating end single contact grouping
Insert Material Specification:
Mil-m-14, ty sdg-f military specification single material response single mating end

160 single mating end single contact grouping Included Contact Type:

Included Contact Quantity:

Round pin single mating end single contact grouping

NSN 5935-01-206-2836

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location
Contact surfaces gold
Precious Material And Weight:
0.160 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.