Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-206-4362

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling strain relief
Overall Length:
3.515 inches
Overall Height:
1.375 inches
Overall Width:
1.375 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.063 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.063 inches
Cable Entrance Diameter:
Between 0.378 inches and 0.625 inches
Distance From Mounting Shoulder To Front Face:
0.891 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
18-4 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
900.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
1250.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
250.0
Shell Type:
Solid



**Connector Locking Method:** 

Externally threaded shell

**Connector Cable Strain Relief Method:** 

Cable clamp

Thready Qty Per Inch (tpi):

18

Thread Size:

1.125 inches

Terminal Location: Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

### **Terminal Type:**

Crimp single mating end single contact grouping

#### Shell Material:

Aluminum

Shell Surface Treatment:

Cadmium and chromate

**Included Contact Quantity:** 

4 single mating end single contact grouping

# Included Contact Type:

Round pin single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

### **Precious Material And Weight:**

0.004 gold grains, troy and 0.004 silver grains, troy

**Precious Material:** 

Gold and silver

**Thread Series Designator:** 

Unef

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0