## NSN 5935-01-206-9994

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-206-9994

Body Style: Straight shape Overall Length: 3.140 inches Overall Diameter: 0.560 inches Environmental Protection: Shock proof and vibration proof Cable Entrance Diameter: 0.280 inches Mating End Quantity: 1 Contact Removability: Removable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Detent Connector Cable Strain Relief Method: Compression nut Terminal Location: Back single mating end single contact grouping
Overall Length: 3.140 inches Overall Diameter: 0.560 inches Environmental Protection: Shock proof and vibration proof Cable Entrance Diameter: 0.280 inches Mating End Quantity: 1 Contact Removability: Removable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Detent Connector Cable Strain Relief Method: Compression nut Terminal Location:
3.140 inches  Overall Diameter: 0.560 inches  Environmental Protection: Shock proof and vibration proof  Cable Entrance Diameter: 0.280 inches  Mating End Quantity: 1  Contact Removability: Removable single mating end single contact grouping  Shell Type: Solid  Connector Locking Method: Detent  Connector Cable Strain Relief Method: Compression nut Terminal Location:
Overall Diameter:  0.560 inches  Environmental Protection: Shock proof and vibration proof  Cable Entrance Diameter: 0.280 inches  Mating End Quantity: 1  Contact Removability: Removable single mating end single contact grouping  Shell Type: Solid  Connector Locking Method: Detent  Connector Cable Strain Relief Method: Compression nut Terminal Location:
Environmental Protection: Shock proof and vibration proof Cable Entrance Diameter: 0.280 inches Mating End Quantity: 1 Contact Removability: Removable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Detent Connector Cable Strain Relief Method: Compression nut Terminal Location:
Environmental Protection: Shock proof and vibration proof  Cable Entrance Diameter: 0.280 inches  Mating End Quantity: 1  Contact Removability: Removable single mating end single contact grouping  Shell Type: Solid  Connector Locking Method: Detent  Connector Cable Strain Relief Method: Compression nut  Terminal Location:
Shock proof and vibration proof  Cable Entrance Diameter:  0.280 inches  Mating End Quantity:  1  Contact Removability: Removable single mating end single contact grouping  Shell Type: Solid  Connector Locking Method: Detent  Connector Cable Strain Relief Method: Compression nut  Terminal Location:
Cable Entrance Diameter:  0.280 inches  Mating End Quantity:  1  Contact Removability: Removable single mating end single contact grouping  Shell Type: Solid  Connector Locking Method: Detent  Connector Cable Strain Relief Method: Compression nut  Terminal Location:
Mating End Quantity:  1 Contact Removability: Removable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Detent Connector Cable Strain Relief Method: Compression nut Terminal Location:
Mating End Quantity:  1 Contact Removability: Removable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Detent Connector Cable Strain Relief Method: Compression nut Terminal Location:
Contact Removability: Removable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Detent Connector Cable Strain Relief Method: Compression nut Terminal Location:
Contact Removability: Removable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Detent Connector Cable Strain Relief Method: Compression nut Terminal Location:
Removable single mating end single contact grouping  Shell Type: Solid  Connector Locking Method: Detent  Connector Cable Strain Relief Method: Compression nut  Terminal Location:
Shell Type: Solid Connector Locking Method: Detent Connector Cable Strain Relief Method: Compression nut Terminal Location:
Solid  Connector Locking Method:  Detent  Connector Cable Strain Relief Method:  Compression nut  Terminal Location:
Connector Locking Method:  Detent  Connector Cable Strain Relief Method:  Compression nut  Terminal Location:
Detent  Connector Cable Strain Relief Method:  Compression nut  Terminal Location:
Connector Cable Strain Relief Method:  Compression nut  Terminal Location:
Compression nut  Terminal Location:
Terminal Location:
Back single mating end single contact grouping
zack chigic maning cha chigic contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic polyethylene single mating end
Terminal Type:
Crimp single mating end single contact grouping
Contact Material Specification:
Qq-c-530, cond ht federal specification single material response single mating end single contact grouping
Shell Material:
Copper alloy
Shell Material Specification:
Qq-b-626, 1/2 h federal specification single material response
Insert Material Specification:
Mil-p-22748, cl b, gr 5 military specification single material response single mating end
Included Contact Quantity:

**Included Contact Type:** 

Coaxial socket single mating end single contact grouping

1 single mating end single contact grouping

## NSN 5935-01-206-9994

Electrical Plug Connector - Page 2 of 2



Precious Material And Location:
Contact surface gold
<b>Precious Material And Weight:</b>
0.005 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-p-22748 spec.