Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-207-0006

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.375 inches
Overall Height:
1.281 inches
Overall Width:
1.281 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.968 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.968 inches
Distance From Mounting Shoulder To Front Face:
0.750 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
7 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thread Size:
1.000 inches
Terminal Location:
Back single mating end single contact grouping



Conner allo	y single mating end single contact grouping
	Inface Treatment:
	mating end single contact grouping
Insert Mate	
	thetic single mating end
-	Inface Treatment Specification:
	I military specification single treatment response single mating end single contact groupin
Terminal T	
	e mating end single contact grouping
Shell Mate	
Aluminum a	
	ice Treatment:
Cadmium	
	ce Treatment Specification:
	ype 1 federal specification single treatment response
	rial Specification:
	ederal specification single material response
	erial Specification:
	deral specification single material response single mating end
	ontact Quantity:
7 single ma	ting end single contact grouping
Included C	ontact Type:
Round sock	tet single mating end single contact grouping
Precious N	laterial And Location:
Contact sur	faces gold
Precious N	laterial And Weight:
0.007 gold	grains, troy
Precious N	laterial:
Gold	
Thread Sei	ies Designator:
Unef	
Shelf Life:	
N/a	
Unit Of Me	asure:
Demilitariz	ation:
No	
Fiig:	
A039b0	
Mil-std (mi	litary Standard):