

View Online at <https://aerobasegroup.com/nsn/5935-01-207-8379>

Body Style:

Angle shape, pcb type

Overall Length:

Between 4.240 inches and 4.260 inches

Overall Height:

0.750 inches

Overall Width:

0.495 inches

Environmental Protection:

Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant

Unthreaded Mounting Hole Diameter:

Between 0.100 inches and 0.105 inches

Distance Between Mounting Facility Centers:

3.950 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

3 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Mating end

Connector Locking Method:

Friction

Operating Temperature Rating:

Between -65.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 1, grade 3 military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 2 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Printed circuit single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sdg-f or type gdi-30f military specification 1st material response single mating end or mil-m-24519, type gpt-30f or gst-40f military specification 2nd material response single mating end

Included Contact Quantity:

105 single mating end single contact grouping

Included Contact Type:

Square socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.105 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-55302/129 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.