

View Online at https://aerobasegroup.com/nsn/5935-01-208-0652

# Thread Class: 2a and 3b

### **Thread Direction:**

Right-hand and right-hand and right-hand

## **Body Style:**

Rectangular shape center screwlock

#### **Overall Length:**

2.780 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.460 inches

#### **Overall Height:**

2.840 inches

#### **Overall Width:**

0.520 inches

#### **Environmental Protection:**

Cold resistant and heat resistant and corrosion resistant and moisture resistant and shock resistant and vibration resistant

## **Unthreaded Mounting Hole Diameter:**

0.125 inches

## Threaded Device Type:

Coupling facility and back shell

### Mating End Quantity:

12

#### **Contact Position Arrangement Style:**

88 single mating end

#### **Polarization Method:**

Polarization boss and guide pin/socket

#### **Connector Locking Method:**

Jackscrew

#### **End Application:**

An-alq184equi

#### Thready Qty Per Inch (tpi):

32 and 32 and 40

#### **Thread Size:**

0.138 inches and 0.138 inches and 0.138 inches

#### Insert Material:

Plastic diallyl phthalate single mating end or plastic epoxy single mating end or plastic phenolic single mating end

#### **Insert Material Specification:**

Mil-m-14, type sdg-f military specification single material response single mating end

# Color:

Green

## **Thread Series Designator:**

Unc and unc and unc



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-m-14 spec.