NSN 5935-01-208-3564

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-208-3564

Body Style: Pcb, external coupling **Overall Length:** 0.448 inches **Overall Height:** 0.240 inches **Overall Width:** 0.240 inches **Environmental Protection:** Cold resistant and heat resistant Center To Center Distance Between Mounting Facilities Parallel To Height: 0.200 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.200 inches **Mating End Quantity: Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Friction Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Contact Surface Treatment Specification:** Mil-g-45204 military specification 1st treatment response single mating end single contact grouping **Terminal Type:** Pin single mating end single contact grouping **Shell Material:** Metal **Included Contact Quantity:** 1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

NSN 5935-01-208-3564

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.