NSN 5935-01-208-3579

35 single mating end single contact grouping

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-208-3579

Body Style: Straight edge type w/card guide **Overall Length:** 4.196 inches **Overall Height:** 1.218 inches **Overall Width:** 0.531 inches **Unthreaded Mounting Hole Diameter:** 0.128 inches **Distance Between Mounting Facility Centers:** 3.934 inches **Board Accommodated Length:** 3.615 inches single board **Board Accommodated Width:** 0.074 inches **Mating End Quantity:** 1 **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 10.0 single mating end single contact grouping **Connector Locking Method:** Friction **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Criticality Code Justification:** Feat **Terminal Type:** Tab, solder lug single mating end single contact grouping **Contact Material Specification:** Qq-b-750, comp a federal specification single material response single mating end single contact grouping **Insert Material Specification:** Mil-m-14f, ty sdg military specification single material response single mating end **Included Contact Quantity:**

NSN 5935-01-208-3579

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Hermaphrodite single mating end single contact grouping
Special Features:
Polorized at position 5
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.035 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:
A039b0

Mil-std (military Standard):

Mil-m-14f spec.