## NSN 5935-01-209-1838

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-209-1838 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape duplex **Overall Width:** 1.750 inches **Environmental Protection:** Heat resistant and salt water resistant **Distance Between Mounting Facility Centers:** 3.281 inches **Threaded Device Type:** Mounting hole **Mating End Quantity: Contact Position Arrangement Style:** 3 all mating ends **Contact Removability:** Nonremovable all mating ends all contact groupings **Contact Maximum Current Rating In Amps:** 15.0 all mating ends all contact groupings **Contact Maximum Ac Voltage Rating In Volts:** 125.0 all mating ends all contact groupings **Polarization Method:** Mating end Thready Qty Per Inch (tpi): 32 **Thread Size:** 

0.138 inches

**Terminal Location:** 

Back all mating ends all contact groupings

**Contact Material:** 

Copper alloy all mating ends all contact groupings

**Terminal Type:** 

Screw all mating ends all contact groupings

**Test Data Document:** 

81348-w-c-596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:** 

Unc

**Specification Data:** 

81348-w-c-596/99 government specification

## NSN 5935-01-209-1838

Electrical Receptacle Connector - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0