Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-209-1838

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape duplex
Overall Width:
1.750 inches
Environmental Protection:
Heat resistant and salt water resistant
Distance Between Mounting Facility Centers:
3.281 inches
Threaded Device Type: Mounting hole
·
Mating End Quantity:
2 Contact Desition Arrangement Style:
Contact Position Arrangement Style:
3 all mating ends
Contact Removability:
Nonremovable all mating ends all contact groupings
Contact Maximum Current Rating In Amps:
15.0 all mating ends all contact groupings
Contact Maximum Ac Voltage Rating In Volts:
125.0 all mating ends all contact groupings
Polarization Method:
Mating end
Thready Qty Per Inch (tpi):
32
Thread Size:
0.138 inches
Terminal Location:
Back all mating ends all contact groupings
Contact Material:
Copper alloy all mating ends all contact groupings
Terminal Type:
Screw all mating ends all contact groupings
Test Data Document:
81348-w-c-596 specification (includes engineering type bulletins, b
excludes commercial catalogs, industry directories, and similar tra

81348-w-c-596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Thread Series Designator:

Unc

## Specification Data:

Electrical Receptacle Connector - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0