Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-209-2785

### **Body Style:**

Straight shape, external coupling

# **Overall Length:**

1.040 inches

# **Overall Height:**

1.688 inches

# **Overall Width:**

1.688 inches

#### **Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

#### **Unthreaded Mounting Hole Diameter:**

Between 0.142 inches and 0.157 inches

# Center To Center Distance Between Mounting Facilities Parallel To Height:

1.375 inches

# Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.375 inches

# Distance From Mounting Shoulder To Front Face:

Between 0.785 inches and 0.790 inches

# Mating End Quantity:

1

Contact Removability:

Removable single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### Insert Position In Deg:

0.0

#### Shell Type:

Solid

#### **Connector Locking Method:**

Bayonet pin

#### End Application:

1430-01-185-3594

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

# **Terminal Type:**

Crimp single mating end single contact grouping



## Shell Material:

Aluminum alloy

Shell Surface Treatment:

Passivate

Included Contact Quantity:

53 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

**Precious Material And Weight:** 

0.053 gold grains, troy

Precious Material:

Gold

#### **Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Specification Data:**

96906-ms27505 government standard

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.