Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-209-5591

## **Body Style:**

Straight edge type w/mounting flange

### **Overall Length:**

3.590 inches

## **Overall Height:**

0.400 inches

**Overall Width:** 

0.745 inches

#### **Environmental Protection:**

Corrosion resistant and fire resistant and shock resistant and thermal shock resistant and vibration resistant

## **Unthreaded Mounting Hole Diameter:**

0.130 inches

### **Distance Between Mounting Facility Centers:**

3.330 inches

### **Board Accommodated Length:**

2.800 inches single board

# Board Accommodated Width:

0.125 inches

## Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

29 single mating end

#### **Contact Removability:**

Removable single mating end single contact grouping

## Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

## Contact Maximum Ac Voltage Rating In Volts:

1800.0 single mating end single contact grouping

## Contact Maximum Dc Voltage Rating In Volts:

1800.0 single mating end single contact grouping

#### **Polarization Method:**

Contact to contact polarizing keys

#### **Connector Locking Method:**

Friction

#### **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate single mating end



# Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact grouping

## Terminal Type:

Crimp single mating end single contact grouping

## Contact Material Specification:

Qq-b-750 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single

material response single mating end single contact grouping

# Insert Material Specification:

Mil-p-19833, type gdi-30f military specification single material response single mating end

# Included Contact Quantity:

29 single mating end single contact grouping

# Included Contact Type:

V-socket single mating end single contact grouping

# Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

## Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.