## NSN 5935-01-209-9464

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-209-9464 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 2.025 inches **Overall Height:** 1.170 inches **Overall Width:** 0.546 inches **Distance Between Mounting Facility Centers:** 1.900 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket and jackscrew **Connector Locking Method:** Jackscrew-socket Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end

**Terminal Type:** 

Wire wrap single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-14, sdg-f military specification single material response single mating end

## NSN 5935-01-209-9464

Electrical Receptacle Connector - Page 2 of 2



## **Included Contact Quantity:** 60 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.060 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** Demilitarization: No Fiig:

A039b0

Mil-m-14 spec.

Mil-std (military Standard):