NSN 5935-01-210-5350

Receptacle Dummy Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-210-5350 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** Between 1.526 inches and 1.556 inches **Overall Height:** 1.135 inches **Overall Width:** Between 0.479 inches and 0.509 inches **Environmental Protection:** Corrosion resistant and humidity resistant and shock resistant and vibration resistant **Distance Between Mounting Facility Centers:** Between 1.307 inches and 1.317 inches **Threaded Device Type:** Mounting hole **Mating End Quantity: Contact Position Arrangement Style:** "2, 15" single mating end **Contact Removability:** Removable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Friction Thready Qty Per Inch (tpi): 40 **Thread Size:** 0.112 inches **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Shell Material:**

Metal

Shell Surface Treatment:

Cadmium and chromate

NSN 5935-01-210-5350

Receptacle Dummy Connector - Page 2 of 2



Shell Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end

Special Features:

Eleven contacts are spliced and have sealing plugs

Precious Material And Location:

Contact surfaces silver

Precious Material And Weight:

0.020 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.