Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-210-6373

| Body Style: |
|---|
| Right angle type |
| Overall Length: |
| 3.265 inches |
| Overall Width: |
| Between 0.473 inches and 0.484 inches |
| Environmental Protection: |
| Cold resistant and heat resistant |
| Unthreaded Mounting Hole Diameter: |
| 0.106 inches |
| Distance Between Mounting Facility Centers: |
| 2.950 inches |
| Mating End Quantity: |
| 1 |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 3.0 single mating end single contact grouping |
| Polarization Method: |
| Guide pin/socket |
| Connector Locking Method: |
| Friction |
| Terminal Location: |
| Side single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and nickel single mating end single contact grouping |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Terminal Type: |
| Pin single mating end single contact grouping |
| Unable To Decode: |
| Unable to decode and unable to decode |
| Included Contact Quantity: |
| 80 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.080 gold grains, troy |

Electrical Receptacle Connector - Page 2 of 2

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

