## NSN 5935-01-210-6374

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-210-6374 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Rectangular shape center screwlock **Overall Length:** 2.950 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.478 inches **Overall Height:** 2.090 inches **Overall Width:** 0.950 inches **Threaded Device Type:** Mounting hole **Mating End Quantity:** 1 **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Polarization boss Shell Type: Solid **Connector Locking Method:** Jackscrew Thready Qty Per Inch (tpi): 40 **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Rubber synthetic single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 2, cl 2 military specification single treatment response single mating end single contact grouping

Crimp single mating end single contact grouping

**Terminal Type:** 

## NSN 5935-01-210-6374

Electrical Receptacle Connector - Page 2 of 2



Shell Material:	
Steel	
Shell Surface Treatment:	
Cadmium and nickel	
Included Contact Quantity:	
100 single mating end single contact grouping	
Included Contact Type:	
Round socket single mating end single contact grouping	
Precious Material And Location:	
Contact surfaces gold	
Precious Material And Weight:	
0.100 gold grains, troy	
Precious Material:	
Gold	
Thread Series Designator:	
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	
<del>.</del>	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Standard):	
Mil-g-45204 spec.	