Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-210-6376

Body Style:

Right angle type

**Overall Length:** 

4.195 inches

## **Overall Height:**

0.758 inches

**Overall Width:** 

0.390 inches

#### **Environmental Protection:**

Cold resistant and heat resistant

#### **Unthreaded Mounting Hole Diameter:**

#### 0.126 inches

**Distance Between Mounting Facility Centers:** 

3.875 inches

Mating End Quantity:

1

## **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

#### Contact Removability:

Removable single mating end single contact grouping

#### **Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

#### Contact Maximum Ac Voltage Rating In Volts:

1300.0 single mating end single contact grouping

#### **Polarization Method:**

Mating end

#### **Connector Locking Method:**

Friction

#### **Terminal Location:**

Side single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Insert Material:**

Glass fiber single mating end and plastic single mating end

#### **Terminal Type:**

Pin single mating end single contact grouping

### **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

#### Insert Material Specification:

Mil-p-46161, grade b, class 15 military specification all material responses single mating end

## Included Contact Quantity:

58 single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-p-46161 spec.