## NSN 5935-01-210-9129

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-210-9129 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Angle shape, external coupling **Bushing Diameter:** 0.162 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 0.340 inches **Overall Height:** 0.605 inches **Overall Width:** 0.500 inches **Unthreaded Mounting Hole Diameter:** 0.102 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.340 inches **Distance From Mounting Shoulder To Rear Face:** 0.109 inches Flange Length: 0.500 inches **Threaded Device Type:** Back shell **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Sma single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** 

Friction

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

## NSN 5935-01-210-9129

Electrical Receptacle Connector - Page 2 of 3



Thready Qty Per Inch (tpi):
36
Thread Size:
0.250 inches
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic polytetrafluoroethylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204, ty ii, gr b, cl 2 military specification 1st treatment response single mating end single contact grouping and mil-c-14550, cl 4
military specification 2nd treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single
material response single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Passivate
Shell Surface Treatment Specification:
Qq-p-35, ty i, ii, or iii federal specification single treatment response
Shell Material Specification:
Qq-s-764, series 303, cond a federal specification single material response
Insert Material Specification:
Mil-p-19468 military specification single material response single mating end
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold

**Unit Of Measure:** 

Uns

N/a

Shelf Life:

**Thread Series Designator:** 

## NSN 5935-01-210-9129

Electrical Receptacle Connector - Page 3 of 3



_					
11	em)	 tor	172	n	

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.