NSN 5935-01-210-9787

Tip Jack - Page 1 of 2

Electrical Insulation Feature:

Mounting Bushing Length:

Uninsulated **Body Style:**Rivet mounted

0.090 inchesBody Length:0.220 inches



View Online at https://aerobasegroup.com/nsn/5935-01-210-9787

| Overall Diameter: |
|---|
| 0.102 inches |
| Bushing Accommodation Hole Shape: |
| Round |
| Accommodated Finger Type: |
| Test prod single finger |
| Finger Accommodation Diameter: |
| 0.040 inches single finger |
| Finger Accommodation Length: |
| 0.185 inches single finger |
| Mounting Bushing Diameter: |
| 0.074 inches |
| Bushing Thru-hole Accommodation Diameter: |
| 0.076 inches |
| Current Rating In Amps: |
| 2.0 |
| Mounting Facility Type And Quantity: |
| 1 bushing |
| Terminal Type: |
| Solder well |
| Material: |
| Brass body |
| Material: |
| Copper alloy spring |
| Precious Material And Location: |
| Contact and body surfaces gold |
| Precious Material: |
| Gold |
| Surface Treatment: |
| Gold and copper spring |
| Surface Treatment: |
| Gold and copper spring |
| Shelf Life: |
| N/a |
| |
| |

NSN 5935-01-210-9787

Tip Jack - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A03400