

View Online at <https://aerobasegroup.com/nsn/5935-01-211-1538>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, flush mount

**Overall Length:**

1.700 inches

**Overall Height:**

Between 1.985 inches and 2.015 inches

**Overall Width:**

Between 3.060 inches and 3.090 inches

**Environmental Protection:**

Humidity resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.118 inches and 0.122 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 1.427 inches and 1.447 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

2.782 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.055 inches and 0.065 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

32c2 2nd mating end

**Contact Removability:**

Nonremovable 2nd mating end 1st contact grouping

**Polarization Method:**

2 polarization posts

**Shell Type:**

Solid

**Connector Locking Method:**

Jackscrew

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.190 inches

**Terminal Location:**

Back 1st mating end single contact grouping

**Contact Material:**

Copper alloy 2nd mating end 1st contact grouping

**Contact Surface Treatment:**

Gold 1st mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate all mating ends

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response 2nd mating end 1st contact grouping

**Terminal Type:**

Solder well 2nd mating end 1st contact grouping

**Guide Design And Location:**

Hexagon shape male post left-hand at 6 oclock and hexagon shape male post right-hand at 6 oclock

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Shell Surface Treatment Specification:**

Qq-p-416, type 2 federal specification all treatment responses

**Shell Material Specification:**

Qq-a-591 federal specification single material response or qq-a-367 federal specification single material response or qq-a-250 federal specification single material response

**Insert Material Specification:**

Mil-m-14 military specification single material response all mating ends

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.136 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.