

View Online at <https://aerobasegroup.com/nsn/5935-01-211-1543>

**Body Style:**

Right angle type

**Overall Length:**

5.628 inches

**Overall Width:**

0.353 inches

**Body Height:**

0.238 inches

**Environmental Protection:**

Corrosion resistant and humidity resistant and shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.093 inches

**Distance Between Mounting Facility Centers:**

5.358 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Polarization Method:**

Contact

**Connector Locking Method:**

Friction

**Terminal Location:**

Side single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Pin single mating end single contact grouping

**Contact Material Specification:**

Qq-b-750 federal specification single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-p-46174 military specification single material response single mating end

**Included Contact Quantity:**

102 single mating end single contact grouping

**Included Contact Type:**

Flat socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.102 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.