## NSN 5935-01-211-3423



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-211-3423 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.300 inches **Overall Height:** 1.343 inches **Overall Width:** 1.343 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.062 inches **Distance From Mounting Shoulder To Front Face:** 0.729 inches **Threaded Device Type:** Back shell **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 18-31 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Bayonet pin **Thread Length:** 

0.290 inches **Thread Size:** 

1.062 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

## NSN 5935-01-211-3423

Electrical Receptacle Connector - Page 2 of 2



## **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy 6061 **Shell Surface Treatment:** Anodize **Included Contact Quantity:** 31 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.025 gold grains, troy and 0.025 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unef **Shelf Life:** N/a **Unit Of Measure: Demilitarization:**

No Fiig: A039b0