

View Online at <https://aerobasegroup.com/nsn/5935-01-211-5073>

Body Style:

Straight shape

Overall Length:

2.088 inches

Overall Height:

0.668 inches

Overall Width:

0.587 inches

Environmental Protection:

Corrosion resistant and humidity resistant and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.120 inches

Distance Between Mounting Facility Centers:

1.852 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Atah "b, 17w2" single mating end

Contact Removability:

Nonremovable single mating end 1st contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Connector Locking Method:

Friction

Terminal Location:

Back single mating end 1st contact grouping

Contact Material:

Copper alloy single mating end 1st contact grouping

Contact Surface Treatment:

Gold single mating end 1st contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-24308, type 2, grade c, class 1 military specification single treatment response single mating end 1st contact grouping

Terminal Type:

Solder well single mating end 1st contact grouping

Shell Material:

Metal

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses

Insert Material Specification:

Mil-m-14, ty gdi-30f or sd6-f military specification single material response single mating end

Included Contact Quantity:

15 single mating end 1st contact grouping

Included Contact Type:

Round socket single mating end 1st contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.015 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-24308 spec.